




HIGH LEVEL
SAFETY



INTERNAL OR
EXTERNAL



10 YEAR
GUARANTEE



SHORT LEAD
TIME



ECO/ENVIRO
FRIENDLY



AVAILABLE IN
5 COLOURS

ALUMINIUM SECURITY SHUTTERS

CARE & MAINTENANCE

Congratulations on choosing Sunflex SA Shutters as your preferred supplier for security shutters. We are proud to offer a 10-year guarantee on our product and encourage any feedback on the product and overall service you received.

All Sunflex SA Security Shutters require ongoing care and maintenance to ensure trouble free operations. The below mentioned cleaning intervals are guidelines, we encourage our clients to use their own discretion to determine when care and maintenance is required.

Note that care and maintenance is required for both inland and coastal installations.

Equipment needed

- 2 x white cotton soft cloths
- Broom with soft bristles or a vacuum cleaner (for cleaning of bottom tracks ONLY)
- Non-acetic multipurpose silicon spray


Weekly cleaning method

- Remove dirt and dust from the bottom track by using a broom or vacuum cleaner. Dirt inside the track will prevent the bottom guide pin from gliding smoothly, causing the shutters to get stuck or make abnormal squeaking or scraping sounds while opening and/or closing them.
- NO lubrication needed for the bottom track.
- Shutters, louvre blades, frames and tracks (top and bottom) should be cleaned with a solution of warm water and non-abrasive, pH neutral detergent solution. Surfaces should be thoroughly rinsed after cleaning to remove all residues. All surfaces should be cleaned using a soft cloth or sponge or nothing harsher than a soft natural bristle brush.
- Dry the shutters by using a non-scratch cloth.





HIGH LEVEL
SAFETY



INTERNAL OR
EXTERNAL



10 YEAR
GUARANTEE



SHORT LEAD
TIME



ECO/ENVIRO
FRIENDLY



AVAILABLE IN
5 COLOURS

ALUMINIUM SECURITY SHUTTERS

CARE & MAINTENANCE continued

Six-monthly lubrication

- Every six months: lubricate all the wheels inside the top track by using a non-acetic multipurpose silicone spray. **CAUTION:** Please read all product instructions and cautions as indicated.
- NO lubrication needed for hinges.
- NO lubrication needed for the bottom track.
- NO lubrication needed for the lock cylinder.

Important information

- Do not use solvents such as thinners, benzene, turpentine, non-recommended household/commercial/industrial cleaners, abrasive cloths and cleaning agents, brushes and/or sponges to clean your shutters as it may affect the powder coating.
- When in doubt please ask your Blockhouse Shutters agent for assistance and/or additional information.
- Report all product related defects to your sales consultant as soon as possible.

